



Mark Bixby  
csy r&d lab  
august 21, 2001

perl programming on  
mpc/ix

# introduction and history

- Practical Extraction and Report Language
  - Pathologically Eclectic Rubbish Lister?
- the Swiss Army chainsaw of scripting languages
- optimized for textprocessing
- combines the best of C, sh, awk, and sed
- released in 1987 by Larry Wall
- initially ported to MPE by Mark Klein
- reported by Mark Bigby in 1997 with periodic updates since then
- "There's more than one way to do it!"

## current status

- Perl release v5.6.0 available for MPE from [bixby.org](http://bixby.org)
- Perl release v5.6.1 available for MPE from [jazz.externalhp.com](http://jazz.externalhp.com)
- Perl is not currently supported by HP, but if your use of Perl uncovers any underlying MPE or POSIX bugs, then we certainly want to hear from you!
- the best way to get assistance with Perl on MPE is to post your questions to HP 3000-L
- CSY is investigating the possibility of offering some future version of Perl as a fully supported product

# Installation

- download from [http://jazz.externalhp.com/sic/hp\\_firmware/perl/](http://jazz.externalhp.com/sic/hp_firmware/perl/)
- edit and run the INSTALL script
- creates a PERL account
- does not use Priv-Mode capability
- /PERL/PUB/perl is the interpreter
  - start scripts with #!/PERL/PUB/perl
  - don't start scripts with #!/PERL/PUB/PERL

# how to execute the interpreter

- From the shell: **/PERL/PUB/perl** [optional parameters]
- As a shellscript: **#!/PERL/PUB/perl** [optional parameters]
- From the CI: **XEQ SH.HPBIN.SYS '-c "/PERL/PUB/perl** [optional parameters]" '
- **-c** - check syntax without doing execution
- **-d** - run the Perl debugger
- **-e** - specify one line of script (like sed)
- **-v** - prints minimal version information
- **-VV** - prints verbose version information
- **-w** - prints VERY useful syntax and runtime warnings; everybody should make a habit of testing their scripts with this!

# variable names

- scalarvalues

- **\$days** # the simple scalarvalue "days"
  - **\$days[ 28 ]** # the 29th element of an array @ days
  - **\$days{ 'Feb' }** # the Feb value from hash % days
  - **\$#days** # the last index of an array @ days

- entire arrays or array slices (aka lists)

- **@days** # (\$days[0], \$days[1], ..., \$days[n])
  - **@days[ 3,4,5 ]** # same as @ days[3..5]
  - **@days{ 'a', 'c' }** # same as (\$days{a}, \$days{c})

- entire hashes

- **%days** # (key1, val1, key2, val2 ...)

# value constructors

- scalar values

- `$abc = 12345;`
- `$abc = 12345.67;`
- `$abc = 0xffff; # hexadecimal`
- `$abc = 0377; # octal`
- `$abc = 'a simple string';`
- `$abc = "a string with a newline\n";`

- list values

- `@abc = ("cat", "dog", $def);`
- `($dev, $ino, undef, undef, $uid, $gid) = stat($file);`

- hash values

- `$abc{'December'} = 12;`
- `$month = $abc{'December'};`

## scalars.listcontext

- the context of some operations will determine the type of the data returned
  - scalar
  - list
- assignment to a scalar variable will evaluate the righthand side in a scalar context
  - \$onerecord = <STDIN>
- assignment to a listvariable will evaluate the righthand side in a list context
  - @entirefile = <STDIN>
- context-based behavior is always documented

# simple statements

- terminated with a semicolon
- may be followed by one optional modifier
  - if** EXPR
  - unless** EXPR
  - while** EXPR
  - until** EXPR
  - foreach** EXPR
- \$os = 'mpe';**
- \$os = 'mpe' if \$model == 3000;**

# compound statements

- a block is a sequence of statements delimited by curly brackets (braces) that defines a scope
- compound statements that control flow:
  - **if (EXPR) BLOCK**
  - **if (EXPR) BLOCK else BLOCK**
  - **if (EXPR) BLOCK elif (EXPR) BLOCK ... else BLOCK**
  - **LABEL while (EXPR) BLOCK**
  - **LABEL while (EXPR) BLOCK continue BLOCK**
  - **LABEL for (EXPR; EXPR; EXPR) BLOCK**
  - **LABEL foreach VAR (LIST) BLOCK**
  - bop control via **next**, **last**, and **redo**
  - **if (\$model == 3000) { \$os = 'mpe' };**

# subroutines

```
sub max {  
    my $max = shift(@_);  
    foreach $foo (@_) {  
        $max = $foo if $max < $foo; }  
    return $max;  
}  
  
$bestday = max($mon,$tue,$wed,$thu,$fri);
```

- parameters passed via @\_ array
  - @\_ [0] = param 1, @\_ [1] = param 2, etc
  - @\_ is an alias (ie. call by reference)
- private variables declared with my
- return or the value of the last expression is the functional return value

# arithmetic operators

- addition: +
- subtraction: -
- multiplication: \*
- division: /
- modulus: %
- exponentiation: \*\*
- auto-increment and -decrement: ++ --
  - **++\$a** - increments \$a, returns new value
  - **\$a++** - returns current value, then increments \$a

# assignment operators

- works like C
  - `$a += 2;` is equivalent to `$a = $a + 2;`
  - `**=   +=   *=   &=   <<=   &&=   -=   /=`
  - `|=    >>=   ||=   .=   %=    ^=    x=`

# relational operators

- numeric comparisons:

- < > <= >= == != <=>

- <=> returns -1, 0, or 1 depending on whether the left argument is numerically less than, equal to, or greater than the right argument

- string comparisons:

- lt gt le ge eq ne cmp

- cmp returns -1, 0, or 1 depending on whether the left argument is stringwise less than, equal to, or greater than the right argument

# bitwise operators

- shift left:`<<`
- shift right:`>>`
- AND:`&`
- OR:`|`
- XOR:`^`
- negation:`~`

# i/o and file handles

- open files are identified via file handles
- uppercase handle names by convention
- predefined file handles: **STDIN, STDOUT, STDERR**
- **<FILEHANDLE>** in a scalar context reads the next record from the file
- **<FILEHANDLE>** in a list context reads ALL of the remaining records from the file
- filenames must be specified using POSIX HFS syntax instead of MPE syntax

# opening files with open()

- `open(HANDLE, "/path/to/file")` # open for reading
- `open(HANDLE, "< /path/to/file")` # open for reading
- `open(HANDLE, "> /path/to/file")` # open for writing
- `open(HANDLE, ">> /path/to/file")` # open for appending
- `open(HANDLE, "| shell command")` # open pipe for writing
- `open(HANDLE, "shell command |")` # open pipe for reading
- Be very careful when passing userdata to open() as a file name!  
Hackers know to try using the special metacharacters listed above.

# a file i/o example

```
#!/PERL/PUB/perl

open(HPSW, "/SYS/PUB/HPSWINFO");          # open for input
$one = <HPSW>;                            # read first line
$two = <HPSW>;                            # read second line
$three = <HPSW>;                           # read third line
@therest = <HPSW>;                         # read all remaining lines
close(HPSW);                                # close the file

open(PATCHES, "> /tmp/MPE.patches"); # open for output
foreach $line (@therest) {                # access each array line
    print PATCHES $line if $line =~ /^MPE/; # print if match
}
close(PATCHES);                            # close the file
```

# regular expressions

- a vast superset beyond standard Unix regexps
- a `?m`odifier to make patterns non-greedy
- zero-width look-ahead and look-behind assertions
- conditional expressions
- extra character class matches:
  - `\w` - match a "word" character (alphanumeric, "\_")
  - `\W` - match a non-word character
  - `\s` - match a whitespace character
  - `\S` - match a non-whitespace character
  - `\d` - match a digit
  - `\D` - match a non-digit
- <http://www.perl.com/pub/doc/manual/html/pod/perlre.html>

# using regular expressions

```
$showme=`callci showme`;

if ($showme =~ /RELEASE: ([A-Z]\.(\\d)(\\d)\\.\\d\\d)/) {
    $release = $1;          # the matching V.UU.FF
    $mpe = "$2.$3";         # the matching U and U (i.e. 7.0)
}

$showme =~ s/LDev/Logical Device/gi; # global substitution
```

- **\$n** contains the value of the n-th matching parenthesized regexp
- the **g** suffix causes a global substitution
- the **i** suffix causes case-insensitive matching

# predefined variables – a partial list

- **\$| or \$OUTPUT\_AUTOFLUSH**
  - By default, all Perl output is buffered (0). To enable automatic flushing, set this variable to 1. Needed when doing MPE IO which is usually unbuffered.
- **\$\$ or \$PID**
  - POSIX PID of the current process
- **\$^O or \$OSNAME**
  - operating system name (in peek)
- **@ARGV**
  - script parameters if any
- **%ENV or \$ENV{varname}**
  - accesses the POSIX environment variables

# built-in functions - a partial list

- Functions for SCALARs or strings
  - chomp, chop, chr, crypt, hex, index, lc, lcfirst, length, oct, ord, pack, qq/STRING/, qq\$STRING\$, reverse, rindex, sprintf, substr, tr///, uc, ucfirst, y///
- Regular expressions and pattern matching
  - m //, pos, quotemeta, s///, split, study, qr//
- Numeric functions
  - abs, atan2, cos, exp, hex, int, bg, oct, rand, sin, sqrt, srand
- Functions for real@ ARRAYS
  - pop, push, shift, splice, unshift
- Functions for listdata
  - grep, join, map, qw/STRING/, reverse, sort, unpack
- Functions for real% HASHes
  - delete, each, exists, keys, values
- Functions for fixed length data or records
  - pack, read, syscall, sysread, syswrite, unpack, vec

# built-in functions (cont.)

- Input and output functions
  - binmode, close, cbse, cbse dir, dbm cbse, dbm open, die, eof, fileno, flock, format, getc, print, printf, read, readdir, rewinddir, seek, seekdir, select, syscall, sysread, sysseek, syswrite, tell, telldir, truncate, warn, write
- Functions for filehandles, files, or directories
  - -X, chdir, chmod, chown, chroot, fcntl, gbb, ioctl, link, lstat, mkdir, open, opendir, readlink, rename, rmdir, stat, symlink, umask, unlink, utime
- Keywords related to the control flow of your perl program
  - caller, continue, die, do, dump, eval, exit, goto, last, next, redo, return, sub
- Keywords related to perl modules
  - do, import, no, package, require, use
- Functions for processes and process groups
  - alarm, exec, fork, getpgid, getppid, getpriority, kill, pipe, qx/STRING/, setpgid, setpriority, sleep, system, times, wait, waitpid
- Time-related functions
  - gmtime, localtime, time, times

## built-in functions (cont.)

- Keywords related to classes and object-orientedness
  - bless, dbm close, dbm open, package, ref, tie, tied, untie, use
- Low-level socket functions
  - accept, bind, connect, getpeername, getsockname, getsockopt, listen, recv, send, setsockopt, shutdown, socket, socketpair
- System V interprocess communication functions
  - msgctl, msgget, msgsnd, semctl, semget, semop, shmctl, shmget, shmread, shmwrtie
- Fetching user and group info
  - endgrent, endhostent, endnetent, endpwent, getgrent, getgrgid, getgrnam, getbgn, getpwent, getpwnam, getpwuid, setgrent, setpwent
- Fetching network info
  - endprotoent, endservent, gethostbyaddr, gethostbyname, gethostent, getnetbyaddr, getnetbyname, getnetent, getprotobyname, getprotobynumber, getprotoent, getservbyname, getservbyport, getservent, sethostent, setnetent, setprotoent, setservent

# object oriented programming

- an object consists of:
  - attributes (data)
  - methods (functions to manipulate the attributes)
- many CPAN modules are object-oriented
- for more info:
  - <http://www.perl.com/pub/2000/12/begperl5.html>
  - <http://www.perl.com/pub/doc/manual/html/pod/perltoothml>

# objectdefinitions example - Foo.pm

```
package Foo;

sub new {                                     # method subroutine
    my ($class_name) = @_;
    my ($self) = {};
    bless ($self, $class_name);
    $self->{'_created'} = 1;
    return $self;
}

sub put {                                      # method subroutine
    my ($self, $data) = @_;
    $self->{_bar} = $data;
}

sub get {                                      # method subroutine
    my ($self) = @_;
    return $self->{_bar};                      # return data from the _bar attribute
}

1;                                              # return code for use statement
```

## object usage example

```
#!/PERL/PUB/perl

use Foo;                      # refers to Foo.pm file

$it = new Foo();                # create a new object
$it->put('hello world');      # use the put method
printf "The value is %s\n", $it->get();    # use the get method
```

# interprocess communications

- POSIX signals between related processes
- named pipes between unrelated processes
  - create named pipes with POSIX m\_kfifo command
- unnamed pipes to child processes
  - create using Perl open() function with "|"
- Internet-domain TCP and UDP sockets
- Unix-domain stream sockets
- SysV IPC - shared memory, semaphores, messages

## sockets - a procedural client example

```
#!/PERL/PUB/perl -w

use Socket;

$proto = getprotobynumber('tcp');           # get protocol number
$ipaddr = inet_aton('localhost');          # get the host's IP address
$port = getservbyname('daytime', 'tcp');    # get port number
$address = sockaddr_in($port, $ipaddr);     # create addr struct
socket(SOCK, PF_INET, SOCK_STREAM, $proto); # create the socket
connect(SOCK, $address);                  # connect to remote host

$timestramp = <SOCK>;                     # read a line of data
print "$timestramp\n";                     # print the results
close(SOCK);                            # close the socket
```

## sockets - an object-oriented client example

```
#!/PERL/PUB/perl -w

use IO::Socket;

# create the socket and connect to the host
$remote = IO::Socket::INET->new(
    Proto  = 'tcp',
    PeerAddr = 'localhost',
    PeerPort = 'daytime');

$timestramp = <$remote>;          # read a line of data from the socket
print "$timestramp\n";            # print the results
close($remote);                  # close the socket
```

# web server cgi - a simple example

```
use CGI qw(:standard);

print header;
print start_html('A Simple Example'),
    h1('A Simple Example'),
    start_form,
    "What's your name? ",textfield('name'),
    p,
    "What's the combination?",
    p,
    checkbox_group(-name=>'words',
                    -values=>[ 'eenie','meenie','minie','moe'],
                    -defaults=>[ 'eenie','minie']),
    p,
    "What's your favorite color? ",
    popup_menu(-name=>'color',
                -values=>[ 'red','green','blue','chartreuse']),
    p,
    submit,
    end_form,
    hr;
```

## web server cgi - a simple example (cont.)

```
if (param()) {  
    print  
        "Your name is ",em(param('name')),  
        p,  
        "The keywords are: ",em(join(" ", param('words'))),  
        p,  
        "Your favorite color is ",em(param('color')),  
        hr;  
}  
print end_html;
```

- <http://stein.cs.hmc.edu/www/software/CGI/formoreinformation>

# mpe as a web client

- it's now possible to write MPE applications that look like web browsers
- perform simple HTTP GET requests, or even complicated HTTP POST requests to fill out remote web forms

```
#!/PERL/PUB/perl  
  
use LWP::Simple;  
  
# read the web page contents into the scalar variable $webpage  
$webpage = get('http://www.bixby.org/mark/perlix.html');
```

- See <http://www.lipro.no/lwp/> for more information

# debugging

- invoke the debugger by starting Perl with the `-d` parameter
  - `#!/PERL/PUB/perl -d`
- examine or modify variables
- single-step execution
- set breakpoints
- list source code
- set actions to be done before a line is executed
  - `a 53 print "DB FOUND $foo\n"`
- debugger terminal I/O may act a bit strangely on MPE

# perl extensions

- binary code residing in an external XML based at run time
- a thin layer of C that allows the Perl interpreter to call compiled code written in other languages
- several extension libraries come bundled with Perl (sockets, POSIX, etc)
- a decent tutorial is available - the examples even work on MPE!
  - <http://www.perl.com/pub/doc/manual/html/pod/perlstut.html>
- this is how you would do it to add support for intrinsics

## comprehensive perl archive network (cpan)

- <http://www.cpan.org/>
- a vast collection of free Perl modules
  - over 2200 modules and 850 megabytes of cool stuff
  - mirrored at more than 100 sites around the world
- typical installation process for a CPAN module:
  - `perl Makefile.PL`
  - `make`
  - `make test`
  - `make install`

## integration with mpe

- for access to MPE commands:
  - `system("callci mpe_command")`
  - ``callci mpe_command``
- integration with Apache via mod\_perl available from
  - <http://www.bixby.org/mark/apacheix.html> (unsupported freeware)
- TurboIMAGE intrinsic functionality available from  
[http://www.cpan.org/modules/by-authors/Ted\\_Ashton/](http://www.cpan.org/modules/by-authors/Ted_Ashton/)
- CIC command, JCW, and variable intrinsic functionality available from  
[http://invent3k.external.hp.com/~MGR\\_HIRSCH/](http://invent3k.external.hp.com/~MGR_HIRSCH/)
- want to increase Perl's integration with MPE?
  - a great opportunity for somebody to write additional MPE-specific Perl extension libraries

# perlresources

- <http://www.perl.com/> - the starting point for all things Perl
- [http://perloreilly.com/news/success\\_stories.html](http://perloreilly.com/news/success_stories.html) - how Perl is being used in real-life situations
- <http://www.perl.com/pub/2000/10/begperl.html> - Beginner's Introduction to Perl
- <http://perl.apache.org/> - The Apache/Perl Integration Project
- <http://jazz.externalhp.com/search/freeware/perl> - for the latest info about Perl on MPE
- Usenetnewsgroups.com p.lang.perl\*

## Join the hp3000-L community!

- Available as a mailing list and as the Usenet newsgroup comp.sys.hp.mpe
- In-depth discussions of all things HP e3000
- Talk with other people using Perl on MPE
  - seek advice, exchange tips & techniques
- Keep up with the latest HP e3000 news
- Interact with CSY
- <http://jazz.externalhp.com/papers/hp3000-info.html>